UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

6250 SS
Safety Shower

STANDARD: IS 10592:2018
Meets ANSI Z358.1

INDUSTRY
Food / Steel
Chemical / Mining
Pharma
Laboratories
Automobile

IDEAL APPLICATIONS
Corrosive Environment
Battery charging areas
Spraying operations
Against Acid / Chemical Spillage
Dipping operations
Hazardous substances dispensing areas



SPECIAL FEATURES

STAINLESS STEEL/ ANTI CORROSIVE | HIGH DELUGE ACTION | EASY OPERATION | EASY MAINTENANCE | FIRST AID AIDING EQUIPMENT | DECONTAMINATION UNIT

SHOWER HEAD

Made of highly visible stainless steel (SS 304), resistant to damage from most acid, alkali and oil

Shower head is between 83" (210 cm) to 87" (220 cm) above floor

PULL ROD

For supply and control of water flow in shower head

Pull rod is within 68" (173 cm) height above floor surface

SHOWER VALVE

Through passage S.S valve that opens automatically when the lever is pulled

The valve stays open until it is manually closed

EYE WASH HEAD

Two high-flow sprays, operated at low pressure, which washes the eye and face

Anti-dust cover protects the head from airborne contaminants and automatically opens with water pressure

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72

UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

EYE WASH BOWL
Highly visible stainless steel resistant to damage from most acid, alkali and oil

SUPPLY WATER CONDITION		MATERIAL	
Supply Water	Drinking / Tepid Water	Pipe	SS
Operating Pressure	2.1 kg / cm^2 (30 psi)	Fitting	SS
Operating Temp	Ambient	Flange	SS

FEATURES
Water inlet connection 1-¼" NB single inlet connection for both shower & eye wash
Water outlet connection – 1-¼" NB
Head shower discharge rate – 84-92 lpm
Push to open valve - connects unit to uninterruptible water supply
Eye wash discharge rate – 30 lpm
Base plate - to hold the shower structure in a stable position (size-180mm)
With foot pedal for hands free operation to supply and control water flow through eye wash head

PACKING	GROSS WEIGHT
1 set per box	21 kg

Udyogi

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72